



Home |CompanyProfile |Products |Enquiry |SiteMap |Download |Contact Us

Container Dolley	General Specification	
Container Dolley	01)length X Breadth 02)Max.Height( with side guide 03)Maximum height of roller 04)Load capacity	2540 mm X 173mm 560 mm 510 mm 1.6 tonnes
	05)For ULD (Pallet)size Base dimensions 6)Max.Running Speed	60.4" X 61.5",60.4" X 47" 15 km/hr
	7) Swivel Motion of Turn Table	360 degrees to each other.
	8)Locking Position of Turn Table 4at	90 degrees in to each other.
	9)No.of tyres 4	4

## **Features**

- 1) Chassis: Made of standard rolled steel sections.
- 2)Turn Table Bearing: One Meter diameter Ball Bearing mounted on chassis.
- 3)Rolled Bed Turn Table: Steel frame carrying galvanized roller, dia 60.3 mm.
- 4)Tyres:Cushion rubber tyres fitted in front steerable & rear rigid axle.
- 5)Steering: Fifth wheel style with Front steerable axle operated by tow bar.
- 6)Front Tow Assembly.
- 7)Rear Spring Loaded Printle hook.
- 8) Spring Loaded Retractable Container Stoppers.
- 9)Side Container guides.

Pallet Dollies are also manufactured as per the clients specification.

11,VASTA HOUSE,GR.FLOOR,JANMABOOMI MARG,
FORT ,MUMBAI-400001 ,INDIA.
TEL:91-22-22844307/22871995/22872449

FAX:91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com